

AKEMI® Colour Charts

Copyright © Akemi, 02/2017

Colour Matching System

Version: 01

UNISTONE	1. Wahl / 1st Choice				2. Wahl / 2nd Choice			
	Colour Code	Colour Bond ¹⁾ Adhesive Art. No.	Composil ²⁾ Silicon Art. No.	Akepox 5010 ³⁾ Adhesive Art. No.	Colour Code	Colour Bond ¹⁾ Adhesive Art. No.	Composil ²⁾ Silicon Art. No.	Akepox 5010 ³⁾ Adhesive Art. No.
Stone Name								
Alaska White (P)	2200 Transp. Magic	46091	40401	10687	- -	-	-	-
Andes Grey (P)	1900 Khaki	47091	40441	-	- -	-	-	-
Belgian Blue (P/L/E)	1020 Black	47003	40408	11461	- -	-	-	-
Bianco (P/L)	1130 White	47014	40404	11463	- -	-	-	-
Bianco Assoluto (P/L)	1130 White	47014	40404	11463	- -	-	-	-
Bianco Carrara (P)	1120 White	47013	40403	11462*	- -	-	-	-
Bianco Extreme (P/L)	1130 White	47014	40404	11463	- -	-	-	-
Bianco Galactica (P)	2200 Transp. Magic	46091	40401	10687	- -	-	-	-
Bruno (P/L)	1940 Khaki	47095	40444	11468*	- -	-	-	-
Cemento (P)	1860 Grey	47087	40438	11467*	- -	-	-	-
Cemento (L)	1880 Grey	47089	40440	11467	- -	-	-	-
Crema Marfil (P)	1720 Beige	47073	40431	11465	- -	-	-	-
Empire Brown (P)	2200 Transp. Magic	46091	40401	10687	- -	-	-	-
Grigio (P/L)	1805 Grey	47082	40433	-	- -	-	-	-
Jura Brown (P)	1940 Khaki	47095	40444	11468*	- -	-	-	-
Jura Grey (P)	2200 Transp. Magic	46091	40401	10687	- -	-	-	-
Moca Crema (P/L)	1725 Beige	47076	40425	11465*	- -	-	-	-
Nero Assoluto (P/L)	1010 Black	47002	40407	11461*	- -	-	-	-
Nero Galactica (P)	1000 Black	47001	40406	11460	- -	-	-	-
Sabbia Greige (P/L)	2200 Transp. Magic	46091	40401	10687	- -	-	-	-
Titanium Brown (P)	2200 Transp. Magic	46091	40401	10687	- -	-	-	-
	- -	-	-	-	- -	-	-	-

1) Epoxyacrylate Adhesive for **Indoor Application** only

2) **Engineered & Natural Stone** Silicone

3) Epoxy Adhesive for **Indoor & Outdoor Application**

* the mentioned **Colour Code** is **not available** in Akepox 5010, the shown Art. Nr. indicates the **closest Akepox 5010 colour**

The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece. Observation of Technical Data Instruction is mandatory (www.akemi.com).

AKEMI chemisch technische Spezialfabrik GmbH

90451 Nuremberg, Lechstraße 28, Germany

info@akemi.com

www.akemi.com