

AKEMI® Colour Charts

Copyright © Akemi, 04/2017

Colour Matching System

Version: 01

MAXFINE Stone Name	1. Wahl / 1st Choice				2. Wahl / 2nd Choice			
	Colour Code	Colour Bond ¹⁾ Adhesive Art. No.	Composil ²⁾ Silicon Art. No.	Akepox 5010 ³⁾ Adhesive Art. No.	Colour Code	Colour Bond ¹⁾ Adhesive Art. No.	Composil ²⁾ Silicon Art. No.	Akepox 5010 ³⁾ Adhesive Art. No.
Black	- -	-	-	-	1860 Grey	47087	40438	11467*
Calacatta	- -	-	-	-	1640 Cream	47065	40418	-
Coffee Truth	2040 Brown	47105	40450	-	1860 Grey	47087	40438	11467*
Corten Nat.	2050 Brown	47106	40451	11469*	- -	-	-	-
Crema Marfil Select	1750 Beige	47078	40427	-	- -	-	-	-
Dark Depth	1020 Black	47003	40408	11461	1880 Grey	47089	40440	11467
Grey Calm	1830 Grey	47084	40435	11466	- -	-	-	-
Ivory Black	1020 Black	47003	40408	11461	1010 Black	47002	40407	11461*
Lavica Beige	1670 Cream	47068	40421	11464	- -	-	-	-
Lavica Dark	1920 Khaki	47093	40442	11468	- -	-	-	-
Lavica Grey	1960 Khaki	47097	40446	-	- -	-	-	-
Onice Oro	1705 Beige	47074	40423	-	- -	-	-	-
Pearl	1890 Grey Magic	46141	40457	-	- -	-	-	-
Pearl Mind	1815 Grey	47083	40434	-	1890 Grey Magic	46141	40457	-
Sand Earth	1725 Beige	47076	40425	11465*	- -	-	-	-
Sand Heart	1750 Beige	47078	40427	-	- -	-	-	-
Thassos	1160 White Magic	46112	40454	-	1100 White	47011	40402	11462
Titanium White Lev.	1130 White	47014	40404	11463	1160 White Magic	46112	40454	-
Titanium White Prelev.	1120 White	47013	40403	11462*	1160 White Magic	46112	40454	-
Turtle Blaze	2010 Brown	47102	40448	-	- -	-	-	-
White	1650 Cream	47066	40419	-	- -	-	-	-
White Purity	1720 Beige	47073	40431	11465	1650 Cream	47066	40419	-
	- -	-	-	-	- -	-	-	-

1) Epoxyacrylate Adhesive for **Indoor Application** only

2) **Engineered & Natural Stone** Silicone

3) Epoxy Adhesive for **Indoor & Outdoor Application**

* the mentioned **Colour Code** is **not available** in Akepox 5010, the shown Art. Nr. indicates the **closest Akepox 5010 colour**

The above information is based on the latest stage of our development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece. Observation of Technical Data Instruction is mandatory (www.akemi.com).

AKEMI chemisch technische Spezialfabrik GmbH

90451 Nuremberg, Lechstraße 28, Germany

info@akemi.com

www.akemi.com